

N 30, Canopy cooker hood, 53 cm, anthracite
D51NAA1COB



COOKING PASSION SINCE 1877



Canopy hood: designed to fit neatly under an overhead unit or cabinet. They're discreet and effectively use valuable space.

- ✓ LED Lighting – Clear illumination while you cook.
- ✓ High extraction rate - for continuously clean air in the kitchen.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

Features

Technical Data

Typology : Built-in/Built-under
Approval certificates : CE
Length of electrical supply cord : 150 cm
Required niche size for installation (HxWxD) : 208mm x 493.0mm x 257mm mm
Minimum distance above an electric hob : 550 mm
Minimum distance above a gas hob : 650 mm
Net weight : 3.670 kg
Type of control : mechanical
Number of speed settings : 3
Maximum output air extraction : 302 m³/h
Maximum output recirculating air : 300 m³/h
Number of lights (Stck) : 2
Noise level : 62 dB(A) re 1 pW
Diameter of air outlet : 120 mm
Grease filter material : Washable aluminium
EAN code : 4242004234432
Connection rating : 121 W
Fuse protection : 5 A
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : GB plug
Installation type : Built-in

Optional accessories

Z51INA0X0 Standard odor filter (replacement)
Z51INTOX0 Standard recirculation kit



4 242004 234432

N 30, Canopy cooker hood, 53 cm, anthracite
D51NAA1COB



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 302 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB*

Features

- Slide control operation
- 3 power levels
- 2 x 3W LED
- Colour Temperature: 2700 K
- 1 metal grease filter cassette
- Installation: Cabinet

Design

- Canopy hood
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit (accessory) needed
- Extraction rate according to EN 61591: max. 302 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB (A) re 1pW
- Power rating: 121 W
- Light Intensity: 78 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 120 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 208-208 x 534 x 300 mm
- Dimensions recirculating (HxWxD): 208-208 x 534 x 300 mm
- Mounting dimensions: width: 49 cm, depth: 26 cm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: D*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 67.7 kWh/year*

Optional accessories

- Recirculating kit Z51INA0X0

* In accordance with the EU-Regulation No 65/2014

N 30, Canopy cooker hood, 53 cm, anthracite
D51NAA1COB

Dimensioned drawings

