

N 50, Canopy cooker hood, 70 cm, Stainless steel
D57MH56NOB



COOKING PASSION SINCE 1877



Canopy hood: designed to fit neatly under an overhead unit or cabinet. They're discreet and effectively use valuable space.

- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ High extraction rate - for continuously clean air in the kitchen.

Features

Technical Data

Typology : Built-in/Built-under
Approval certificates : CE, VDE
Length of electrical supply cord : 150 cm
Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm mm
Minimum distance above an electric hob : 500 mm
Minimum distance above a gas hob : 650 mm
Net weight : 9.057 kg
Type of control : Electronic
Maximum output air extraction : 630 m³/h
Boost position output recirculating : 664 m³/h
Maximum output recirculating air : 571 m³/h
Boost position air extraction : 730 m³/h
Number of lights (Stck) : 2
Noise level : 66 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242004187769
Connection rating : 277 W
Fuse protection : 3 A
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : GB plug
Installation type : Built-in

Optional accessories

| | |
|-----------|--|
| Z5135X1 | Standard odor filter (replacement) |
| Z5135X3 | Standard recirculation kit |
| Z511TD1X1 | Long Life recirculation kit external |
| Z511XB1X6 | Clean Air Plus odor filter (replacement) |
| Z511XC1X6 | Clean Air Plus recirc. kit external |



4 242004 187769

Features

Features

- LED display
- 2 x 1W LED lights
- 2 metal grease filter cassettes
- Stainless steel filter cover, metal grease filter
- 3 speeds plus intensive
- Automatic intensive revert (6mins)
- Rim ventilation

Design

- Stainless steel
- Canopy hood
- Standard design
- Soft touch control
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 630 m³/h
Intensive 730 m³/h
- Power rating: 277 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 66 dB (A) re 1pW
- Noise max. Normal Level: Noise, max. speed in normal us: 66 dB dB*
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 571 m³/h
Intensive: 664 m³/h
Noise level in recirculation mode:
Max. normal use: 72 dB(A) re 1 pW
Intensive: 75 dB(A) re 1 pW
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Dimensions recirculating (HxWxD): 418-418 x 700 x 300 mm
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 104.2 kWh/year*

Optional accessories

- Recirculating kit Z5135X1
- Max. extraction rate: 730 m³/h
- Dimensions (HxWxD): 418 x 700 x 300 mm

* In accordance with the EU-Regulation No 65/2014

N 50, Canopy cooker hood, 70 cm, Stainless steel
D57MH56N0B

Dimensioned drawings

