

N 90, Canopy cooker hood, 70 cm, clear glass black printed
D57ML67N1B



COOKING PASSION SINCE 1877



A++



Canopy hood: designed to fit neatly under an overhead unit or cabinet. They're discreet and effectively use valuable space.

- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air
- ✓ Automatic After-running – ventilation continues for several minutes after you turn it off

Features

Technical Data

Typology : Built-in/Built-under
 Approval certificates : Australia Standards, CE, VDE
 Length of electrical supply cord : 150 cm
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm mm
 Minimum distance above an electric hob : 500 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 9.363 kg
 Type of control : Electronic
 Maximum output air extraction : 575 m³/h
 Boost position output recirculating : 722 m³/h
 Maximum output recirculating air : 533 m³/h
 Boost position air extraction : 775 m³/h
 Number of lights (Stck) : 2
 Noise level : 64 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242004237938
 Connection rating : 172 W
 Fuse protection : 3 A
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

Z5135X1	Standard odor filter (replacement)
Z5135X3	Standard recirculation kit
Z511TD1X1	Long Life recirculation kit external
Z511XB1X6	Clean Air Plus odor filter (replacement)
Z511XC1X6	Clean Air Plus recirc. kit external



4 242004 237938

N 90, Canopy cooker hood, 70 cm, clear glass black
printed
D57ML67N1B



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: A++ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 575 m³/h
Intensive 775 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB*

Features

- LED display
- Soft touch control
- 3 speeds plus intensive
- Automatic intensive revert (6mins)
- 2 x 1W LED lights
- softLight with dimmer function
- Interval operation
- EfficientDrive BLDC technology
- Automatic after running (Automatic after running (30 mins))
- 2 metal grease filter cassettes
- Saturation indicator for grease filter
- No

Design

- Canopy hood
- Installation: Cabinet
- Filter cover glass, metal grease filter
- Electronic controls
- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 775 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 64 dB(A) re 1 pW
Intensive: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 533 m³/h
Intensive: 722 m³/h
Noise level in recirculation mode:
Max. normal use: 71 dB(A) re 1 pW
Intensive: 77 dB(A) re 1 pW
- Power rating: 172 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 30.3 kWh/year*
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm

Optional accessories

* In accordance with the EU-Regulation No 65/2014

N 90, Canopy cooker hood, 70 cm, clear glass black printed
 D57ML67N1B

Dimensioned drawings

