

N 50, Wall-mounted cooker hood, 90 cm, Stainless steel
D94QFM1N0B



COOKING PASSION SINCE 1877



A

Our classic design hood with a modern twist - experience the slim pyramid hood.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

Features

Technical Data

Typology : Wall-mounted
Approval certificates : CE, E17D UKCA marking, VDE
Length of electrical supply cord : 130 cm
Height of the chimney : 582-912/582-1022 mm
Height of product, without chimney : 94 mm
Minimum distance above an electric hob : 550 mm
Minimum distance above a gas hob : 650 mm
Net weight : 11.963 kg
Type of control : Electronic
Maximum output air extraction : 389 m³/h
Boost position output recirculating : 441 m³/h
Maximum output recirculating air : 337 m³/h
Boost position air extraction : 642 m³/h
Number of lights (Stck) : 2
Noise level : 61 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242004224211
Connection rating : 220 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation type : Wall-mounted

Optional accessories

| | |
|-----------|--|
| Z51DXA0X0 | Standard odor filter (replacement) |
| Z51DXI1X6 | Clean Air Plus recirculation kit |
| Z51DXU0X0 | Standard recirculation kit |
| Z51FXC1N6 | Clean Air Plus recirc. kit external |
| Z51FXJ0X0 | Long Life recirculation kit |
| Z53XXB1X6 | Clean Air Plus odor filter (replacement) |
| Z5895N0 | Stainless steel back panel 900 mm |
| Z5905N0 | Chimney extension 1000 mm |
| Z5915N0 | Chimney extension 1500 mm |



4 242004 224211

N 50, Wall-mounted cooker hood, 90 cm, Stainless steel
D94QFM1NOB



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 389 m³/h
Intensive 642 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 61 dB dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Installation: wall

Design

- Chimney hood
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 642 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 61 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 61 dB(A) re 1 pW
Intensive: 70 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 61 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 337 m³/h
Intensive: 441 m³/h
Noise level in recirculation mode:
Max. normal use: 70 dB(A) re 1 pW
Intensive: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 214 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 676-1006 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 676-1116 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
744 x 900 x 500 mm - mounting with outer chimney
874-1204 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 42.4 kWh/year*

Optional accessories

- Recirculating kit Z50XXP0X0

* In accordance with the EU-Regulation No 65/2014

