

N 70, Wall-mounted cooker hood, 90 cm, Stainless steel  
D95BMP5N0B



COOKING PASSION SINCE 1877



The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Special Noise Insulation – For a quiet cooking area.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button

#### Features

##### Technical Data

Typology : Wall-mounted  
 Approval certificates : CE, E17D UKCA marking, VDE  
 Length of electrical supply cord : 130 cm  
 Height of the chimney : 582-908/568-1018 mm  
 Height of product, without chimney : 46 mm  
 Minimum distance above an electric hob : 550 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 19.864 kg  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction : 427 m<sup>3</sup>/h  
 Boost position output recirculating : 442 m<sup>3</sup>/h  
 Maximum output recirculating air : 343 m<sup>3</sup>/h  
 Boost position air extraction : 702 m<sup>3</sup>/h  
 Number of lights (Stck) : 3  
 Noise level : 55 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable stainless steel  
 EAN code : 4242004234913  
 Connection rating : 145 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : GB plug  
 Installation type : Wall-mounted

#### Optional accessories

Z5102X5	Standard recirculation kit
Z51CXC2N6	Clean Air Plus recirc. kit external
Z51CXI1X6	Clean Air Plus recirculation kit
Z51FXJ0X5	Long Life recirculation kit
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5895N0	Stainless steel back panel 900 mm
Z5906N1	Chimney extension 1000 mm
Z5916N1	Chimney extension 1500 mm



N 70, Wall-mounted cooker hood, 90 cm, Stainless steel  
D95BMP5NOB



COOKING PASSION SINCE 1877

## Features

### Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate exhaust air according to EN 61591: max. normal use 427 m<sup>3</sup>/h, intensive 702 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 55 dB dB\*

### Features

- Stainless steel
- Electronic controls
- Touch control
- Interval operation
- Noise reduction function
- Efficient BLDC technology
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- SoftLight with dimmer function
- 3 x 1,5W LED
- Automatic after running (Automatic after running (10 minutes))
- Saturation indicator for metal and charcoal filter
- 3 metal grease filter cassettes
- Steel filter cover
- Installation system: Chimney hood wall fixing syst.

### Design

- 90 cm wide
- Chimney hood
- Installation: wall
- easy to clean Inner frame

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 427 m<sup>3</sup>/h Intensive 702 m<sup>3</sup>/h
- Maximum extraction rate exhaust air 427 m<sup>3</sup>/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 55 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 55 dB(A) re 1 pW Intensive: 66 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches: Extraction rate in recirculation mode: Max. normal use: 343 m<sup>3</sup>/h Intensive: 442 m<sup>3</sup>/h Noise level in recirculation mode: Max. normal use: 66 dB(A) re 1 pW Intensive: 70 dB(A) re 1 pW
- Power rating: 145 W
- Light Intensity: 359 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 33.6 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Electrical cable length 1.3 m
- Dimensions recirculating with CleanAir module (HxWxD): 689 x 898 x 500 mm - mounting with outer chimney 795-1139 x 898 x 500 mm - mounting with telescopic chimney
- Additional noise insulation
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Max. extraction rate: 702 m<sup>3</sup>/h
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm

\* In accordance with the EU-Regulation No 65/2014

N 70, Wall-mounted cooker hood, 90 cm, Stainless steel  
D95BMP5N0B

Dimensioned drawings

