

**Serie | 4, Wall-mounted cooker hood,  
60 cm, Stainless steel  
DWB66DM50B**



**B**

**Box design hood: performance and  
matching kitchen design complete in one  
hood.**

- **Especially silent:** maximum hood performance, minimum noise.
- **Grease filtration level:** filters out over 85% of the grease from kitchen air.
- **TouchSelect control:** Quickly select hood settings via touch.
- **LED illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.

**Technical Data**

Typology : Wall-mounted

Approval certificates : CE, E17D UKCA marking, VDE

Length of electrical supply cord : 130 cm

Height of the chimney : 583-912/583-1022 mm

Height of product, without chimney : 53 mm

Minimum distance above an electric hob : 550 mm

Minimum distance above a gas hob : 650 mm

Net weight : 11.271 kg

Type of control : Electronic

Maximum output air extraction : 368 m<sup>3</sup>/h

Boost position output recirculating : 441 m<sup>3</sup>/h

Maximum output recirculating air : 337 m<sup>3</sup>/h

Boost position air extraction : 605 m<sup>3</sup>/h

Number of lights (Stck) : 2

Noise level : 60 dB(A) re 1 pW

Diameter of air outlet : 120 / 150 mm

Grease filter material : Washable aluminium

EAN code : 4242005051045

Connection rating : 220 W

Fuse protection : 10 A

Voltage : 220-240 V

Frequency : 50; 60 Hz

Plug type : GB plug

Installation type : Wall-mounted

**Optional accessories**

DHZ1225 : Chimney extension 1000 mm

DHZ1235 : Chimney extension 1500 mm

DHZ6551 : Brushed steel back panel

DWZ0DX0AO : Standard odor filter (replacement)

DWZ0DX0U0 : Standard recirculation kit

DWZ0XX0J0 : Long Life recirculation kit

DWZ1DX1I6 : Clean Air Plus recirculation kit

DWZ1FX5C6 : Clean Air Plus recirc. kit external

DZZ1XX1B6 : Clean Air Plus odor filter (replacement)



4 242005 051045

## Serie | 4, Wall-mounted cooker hood, 60 cm, Stainless steel DWB66DM50B

### Box design hood: performance and matching kitchen design complete in one hood.

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 368 m<sup>3</sup>/h  
Intensive 605 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB\*

#### Features

- TouchControl with Electronic display
- Electronic display
- 3 power levels & intensive setting
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 removable metal grease filter cassettes
- Installation: wall

#### Design

- Chimney extractor hood
- TouchControl
- Electronic control

#### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 605 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 60 dB(A) re 1 pW  
Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:  
Extraction rate in recirculation mode:  
Max. normal use: 337 m<sup>3</sup>/h  
Intensive: 441 m<sup>3</sup>/h  
Noise level in recirculation mode:  
Max. normal use: 70 dB(A) re 1 pW  
Intensive: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 242 lux
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 600 x 500 mm - mounting with outer chimney  
833-1163 x 600 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 48.1 kWh/year\*

#### Optional accessories

- Recirculating kit DWZ0DX0A0
- \* In accordance with the EU-Regulation No 65/2014

**Serie | 4, Wall-mounted cooker hood, 60 cm,  
Stainless steel  
DWB66DM50B**

