

**Serie | 2, Wall-mounted cooker hood,  
90 cm, Stainless steel  
DWB94BC50B**



**D**

**Box design hood: performance and  
matching kitchen design complete in one  
hood.**

- **Silent:** maximum extractor performance with minimal noise.
- **LED illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- An impressive extraction rate of m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- Dishwasher safe aluminum mesh filters

**Technical Data**

Typology : Wall-mounted  
Approval certificates : CE, E17D UKCA marking, VDE  
Length of electrical supply cord : 130 cm  
Height of the chimney : 583-912/583-1022 mm  
Height of product, without chimney : 53 mm  
Minimum distance above an electric hob : 550 mm  
Minimum distance above a gas hob : 650 mm  
Net weight : 11.510 kg  
Type of control : mechanical  
Number of speed settings : 3  
Maximum output air extraction : 365 m<sup>3</sup>/h  
Maximum output recirculating air : 240 m<sup>3</sup>/h  
Number of lights (Stck) : 2  
Noise level : 64 dB(A) re 1 pW  
Diameter of air outlet : 120 / 150 mm  
Grease filter material : Washable aluminium  
EAN code : 4242005051106  
Connection rating : 100 W  
Fuse protection : 10 A  
Voltage : 220-240 V  
Frequency : 50; 60 Hz  
Plug type : GB plug  
Installation type : Wall-mounted

**Optional accessories**

DHZ1225 : Chimney extension 1000 mm  
DHZ1235 : Chimney extension 1500 mm  
DHZ9551 : Brushed steel back panel  
DWZ0DX0AO : Standard odor filter (replacement)  
DWZ0DX0U0 : Standard recirculation kit  
DWZ0XX0J0 : Long Life recirculation kit  
DWZ1DX1I6 : Clean Air Plus recirculation kit  
DWZ1FX5C6 : Clean Air Plus recirc. kit external  
DZZ1XX1B6 : Clean Air Plus odor filter (replacement)



4 242005 051106

## Serie | 2, Wall-mounted cooker hood, 90 cm, Stainless steel DWB94BC50B

\* In accordance with the EU-Regulation No 65/2014

### Box design hood: performance and matching kitchen design complete in one hood.

---

#### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB\*

#### Features

- Push button control
- 3 power levels
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- 3 removable metal grease filter cassettes
- Installation: wall

#### Design

- Chimney extractor hood
- Push button control for extractor speeds and light
- Mechanical

#### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Maximum extraction rate exhaust air 365 m<sup>3</sup>/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Power rating: 100 W
- Light Intensity: 91 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500 mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*
- Average Energy Consumption: 53.1 kWh/year\*

#### Optional accessories

- Recirculating kit DHZ9550

**Serie | 2, Wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB94BC50B**

