

**Serie | 4, Wall-mounted cooker hood,  
90 cm, Stainless steel  
DWB96DM50B**



**B**

**Box design hood: performance and matching kitchen design complete in one hood.**

- **Especially silent:** maximum hood performance, minimum noise.
- **TouchSelect control:** Quickly select hood settings via touch.
- **LED illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.
- An impressive extraction rate of m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.

**Technical Data**

Typology : Wall-mounted  
 Approval certificates : CE, E17D UKCA marking, VDE  
 Length of electrical supply cord : 130 cm  
 Height of the chimney : 583-912/583-1022 mm  
 Height of product, without chimney : 53 mm  
 Minimum distance above an electric hob : 550 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 12.310 kg  
 Type of control : Electronic  
 Maximum output air extraction : 372 m<sup>3</sup>/h  
 Boost position output recirculating : 441 m<sup>3</sup>/h  
 Maximum output recirculating air : 337 m<sup>3</sup>/h  
 Boost position air extraction : 604 m<sup>3</sup>/h  
 Number of lights (Stck) : 2  
 Noise level : 60 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242005051120  
 Connection rating : 220 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : GB plug  
 Installation type : Wall-mounted

**Optional accessories**

DHZ1225 : Chimney extension 1000 mm  
 DHZ1235 : Chimney extension 1500 mm  
 DHZ9551 : Brushed steel back panel  
 DWZ0DX0AO : Standard odor filter (replacement)  
 DWZ0DX0U0 : Standard recirculation kit  
 DWZ0XX0J0 : Long Life recirculation kit  
 DWZ1DX1I6 : Clean Air Plus recirculation kit  
 DWZ1FX5C6 : Clean Air Plus recirc. kit external  
 DZZ1XX1B6 : Clean Air Plus odor filter (replacement)



## Serie | 4, Wall-mounted cooker hood, 90 cm, Stainless steel DWB96DM50B

### Box design hood: performance and matching kitchen design complete in one hood.

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Maximum extraction rate exhaust air 372 m<sup>3</sup>/h according to EN 61591
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 372 m<sup>3</sup>/h  
Intensive 604 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB\*

#### Features

- TouchControl with Electronic display
- Electronic display
- 3 power levels & intensive setting
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 3 removable metal grease filter cassettes
- Installation: wall

#### Design

- Chimney extractor hood
- TouchControl
- Electronic control

#### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 604 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 60 dB(A) re 1 pW  
Intensive: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:  
Extraction rate in recirculation mode:  
Max. normal use: 337 m<sup>3</sup>/h  
Intensive: 441 m<sup>3</sup>/h  
Noise level in recirculation mode:  
Max. normal use: 70 dB(A) re 1 pW  
Intensive: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 214 lux
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500 mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 48.5 kWh/year\*

#### Optional accessories

- Recirculating kit DWZ1FX5C6
- \* In accordance with the EU-Regulation No 65/2014

**Serie | 4, Wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB96DM50B**

