

N 70, Island cooker hood, 90 cm, Stainless steel
196BMP5N0B



COOKING PASSION SINCE 1877



A+



The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Special Noise Insulation – For a quiet cooking area.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button

Features

Technical Data

Typology : Island/Ceiling
Approval certificates : CE, E17D UKCA marking, VDE
Length of electrical supply cord : 130 cm
Height of the chimney : 698-878/698-998 mm
Height of product, without chimney : 46 mm
Minimum distance above an electric hob : 550 mm
Minimum distance above a gas hob : 650 mm
Net weight : 30.444 kg
Type of control : Electronic
Number of speed settings : 3-stage + 2 intensive
Maximum output air extraction : 445 m³/h
Boost position output recirculating : 457 m³/h
Maximum output recirculating air : 353 m³/h
Boost position air extraction : 867 m³/h
Number of lights (Stck) : 4
Noise level : 54 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable stainless steel
EAN code : 4242004234982
Connection rating : 166 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation type : Island

Optional accessories

Z5106X5	Standard recirculation kit
Z52CBD2X1	Long Life recirculation kit external
Z52CXC2N6	Clean Air Plus recirc. kit external
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5909N1	Chimney extension 1100 mm



4 242004 234982

Features

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 445 m³/h
Intensive 867 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 54 dB dB*

Features

- Touch control
- 3 power levels and 2 intensive settings
- 4 x 1.5w LED Light
- softLight with dimmer function
- Efficient BLDC-technology
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Noise reduction function
- Additional noise insulation
- easy to clean Inner frame

Design

- Island chimney hood
- Installation: Ceiling
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 867 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 54 dB(A) re 1 pW
Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 353 m³/h
Intensive: 457 m³/h
Noise level in recirculation mode:
Max. normal use: 67 dB(A) re 1 pW
Intensive: 71 dB(A) re 1 pW
- Power rating: 166 W
- Light Intensity: 423 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 31.6 kWh/year*

Optional accessories

- Recirculating kit Z50XXPOX0

* In accordance with the EU-Regulation No 65/2014

Dimensioned drawings

