

Serie | 4, Free-standing fridge-freezer with freezer at bottom, 203 x 70 cm, White KGN49XWEA





Included accessories 3 x egg tray 1 x ice cube tray

your freezerNoFrost: you'll never have to defrost your fridge-freezer again.

A G E • **VitaFresh:** keeps food fresh for longer in climate controlled drawers at near 0°C.

NoFrost bottomfreezer : no need to defrost

- **Perfect Fit:** place your fridge right next to walls and other appliances to save space.
- \bullet LED lights bring a completely new lighting concept to fridges
- **VarioZone:** more flexibility due to variable-use glass shelves and drawers in the freezer compartment.

Technical Data

Energy Efficiency Class: E Average annual energy consumption in kilowatt hour per year (kWh/a): 259 kWh/annum Sum of volume of frozen compartments: 108 l Sum of volume of chill compartments: 330 l Airborne acoustical noise emissions : 40 dB(A) re 1 pW Airborne acoustical noise emission class: C Construction type: Free-standing Door panel options: Not possible Width of the appliance: 700 mm Depth of the product: 670 mm Net weight: 82.530 kg Connection rating: 100 W Fuse protection: 10 A Door hinge: Right reversible Voltage: 220-240 V Frequency: 50 Hz Approval certificates: CE, VDE Length of electrical supply cord: 240 cm Storage Period in Event of Power Failure (h): 16 h Number of compressors: 1 Number of independent cooling systems: 2 Interior ventilator: No Reversible Door Hinge: Yes Number of Adjustable Shelves in fridge compartment (Stck): 4 Shelves for Bottles: Yes Installation type: N/A





Serie | 4, Free-standing fridge-freezer with freezer at bottom, 203 x 70 cm, White KGN49XWEA

NoFrost bottomfreezer : no need to defrost your freezer

- KGN49XWEA
- No Frost, Fridge freezer
- Cambered door, High-door design White

Design features

- White doors and white side panels
- Integrated vertical handle
- Right hinged door, door reversible
- Separate, electronic temperature control with LED display

Food freshness system

- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity

Key features - Fridge section

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer
 2 VitaFresh ◄0°C► drawers with temperature control - Fish and meat stay fresh for longer
- MultiAirflow system improves circulation of air around the fridge
- Bright interior LED fridge light
- 5 safety glass shelves (4 height adjustable)
- Door shelves in fridge door: 1 large and 3 small.
- Super Cooling: automatic deactivation
- Metal bottle rack

Key features - Freezer section

- No Frost, never have to defrost ever again
- 3 freezer drawers
- SuperFreeze function with automatic deactiviation
- Calendar frozen food
- Freezer malfunction warning signal: optical and acoustical warning system

Additional features

- Optical and accoustical
- Vario Zone removable safety glass shelves for extra space!
- 3 x egg tray, 1 x ice cube tray

Dimension and installation

- Connection value 100 W
- 220 240 V
- Height adjustable front feet
- Dimensions: 203 cm H x 70 cm W x 67 cm D
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.

Functions

Performance and Consumption

- EU19_EEK_D: E
- Total Volume : 438 l
- Net Fridge Volume : 330 l
- Net Freezer Volume : 108 l
- Freezing capacity 24h : 12 kg
- Annual Energy Consumption: 259 kWh/a
- Climate Class: SN-T
- EU19_Fast freezer facility_D
- Noise Level : 40 dB , EU19_Noise emission class_D: C
- Temperature rise time : EU19_Temperature rise time_D: 16 H



Serie | 4, Free-standing fridge-freezer with freezer at bottom, 203 x 70 cm, White KGN49XWEA

	Appliance name	а	b	С	d	e	f	g	h	
	KGN 46 (Outer handle)	1860	700	670	590	740	1310	710	12	
	KGN 46 (Inner handle)	1860	700	670	590	710	1310	670	12	
	KGN 49 (Outer handle)	2030	700	670	590	740	1310		12	
	KGN 49 (Inner handle)	2030	700	670	590	710	1310	670	12	
	Description									
	a Height									
	b Widh									
	c Depth with door closed, without handle									
	d Cabinet depth									
	e Width with door opened to 90°									
	f Depth with door opened, without handle									
	g Depth with door closed, with handle									
	h Air gap for installation in recess or fitted cabinet									
						measurements in mm				