

Serie | 6, Gas hob, 60 cm, Stainless steel PCP6A5B90





The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Continuous cast-iron pan support: for high firmness and stability of cookware.
- **Biomethane-ready:** your gas hob can also be powered with renewable biomethane gas.
- Ergonomic control knobs with raised center for precise adjustments.
- Surface colour: elegant stainless-steel design.

Technical Data

Product name/family: gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time: 4

Type of control setting devices: sword knobs

Required niche size for installation (HxWxD) : 45 x 560-562 x

480-492 mm

Width of the appliance : 582 mm Dimensions : 45 x 582 x 520 mm

Dimensions of the packed product (HxWxD): 141 x 651 x 578

mm

Net weight : 10.639 kg Gross weight : 11.5 kg

Residual heat indicator: without Location of control panel: Hob front Basic surface material: Stainless steel Color of surface: Stainless steel Color of frame: Stainless steel

Approval certificates : CE, Eurasian, Morocco Length of electrical supply cord : 100 cm

EAN code : 4242002837468 Electrical connection rating : 1 W Gas connection rating : 7500 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz





Serie | 6, Gas hob, 60 cm, Stainless steel PCP6A5B90

The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:
- Left front: standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Liquid gas G30,31 28-30/37mbar Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW



Serie | 6, Gas hob, 60 cm, Stainless steel PCP6A5B90

