

COOKING PASSION SINCE 1877



Gas hob with side-mounted controls.

- $\sqrt{\,}$ Pan Supports continuous cast-iron finish pan supports for maximum stability and cooking convenience.
- $\sqrt{\,}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.
- $\sqrt{}$ Coating black enamel coating.

Features

Technical Data

Product name/family: gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time : 4

Type of control setting devices : sword knobs

Required niche size for installation (HxWxD) : $45 \times 560-562 \times 10^{-2}$

480-492 mm

Width of the appliance : 580 $\,$ mm $\,$ Dimensions : 45 x 580 x 510 $\,$ mm

Dimensions of the packed product (HxWxD) : $141 \times 651 \times 578 \text{ mm}$

Net weight: 7.497 kg Gross weight: 8.4 kg

Residual heat indicator : without Location of control panel : Hob lateral Basic surface material : Enamel Color of surface : Black

Color of frame : Black Approval certificates : CE

Length of electrical supply cord: 100 cm

EAN code : 4242004187813 Electrical connection rating : 1 W Gas connection rating : 7400 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 60; 50 Hz





Features

Design

- enamel surface, black
- Cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: High-speed burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: Standard burner up to 1.7 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 56 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW



Dimensioned drawings

