







The gas hob with a stainless-steel surface design and adjustable FlameSelect.

- $\sqrt{\mbox{ FlameSelect}^{\mbox{\scriptsize @}}}$ Gain ultimate control of your flame.
- $\sqrt{\ }$ Pan Supports continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{\mbox{ Wok Burner}}$ powerful cooking at up to 4 kW.
- $\sqrt{\,}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.
- $\sqrt{\ }$ Stainless steel surface elegant and sophisticated design.

Features

Technical Data

Product name/family : gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time : 5

Type of control setting devices : sword knobs

Required niche size for installation (HxWxD) : $45 \times 560-562 \times 10^{-2}$

480-492 mm

Width of the appliance : 750 mm Dimensions : $45 \times 750 \times 520$ mm

Dimensions of the packed product (HxWxD) : $145 \times 793 \times 597 \,$ mm

Net weight: 14.043 kg Gross weight: 15.5 kg

Residual heat indicator : without Location of control panel : Hob front Basic surface material : Stainless steel Color of surface : Stainless steel Color of frame : Stainless steel Approval certificates : CE

Length of electrical supply cord: 100 cm

EAN code : 4242004203506 Electrical connection rating : 1 W Gas connection rating : 11500 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 60; 50 Hz





Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 53 x 750 x 520
- Required niche size for installation (HxWxD mm): 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 11.5 KW





