





Optional accessories

Z943SE0 Set of 2 pots and 1 pan

Induction cooktop with TouchControl.

- $\sqrt{}$ Touch Control Control your hob with a simple touch.
- $\sqrt{}$ Combi Induction Merge two circular cooking zones to heat large cookware.
- $\sqrt{}$ Power Move Just slide your cookware to adjust the temperature.
- $\sqrt{\,}$ Power Boost An extra surge of heat when you need fast results.
- $\sqrt{\ }$ Induction the heat is generated directly in the cookware for precise cooking that stops when power is off.

Feature:

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : $51 \times 750-750 \times 10^{-2}$

490-500 mm

Width of the appliance : 802 mm Dimensions : $51 \times 802 \times 522 \text{ mm}$

Dimensions of the packed product (HxWxD) : $126 \times 953 \times 608$ mm

Net weight : 15.290 kg Gross weight : 16.7 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic

Color of surface : Black

Approval certificates : AENOR, CE Length of electrical supply cord : 110 cm

EAN code : 4242004232841

Electrical connection rating: 7400 W

Voltage: 220-240 V Frequency: 50; 60 Hz





Features

Design

- Bevelled front edge
- 80 cm: space for 5 pots or pans.

Flexibility of cooking zones

- Combi zone
- : use bigger cookware by connecting two classic cooking zones into one large zone.
- Cooking zone front left: 180 mm, 1.8 KW (max. power 3.1 KW)
- Cooking zone rear left: 145 mm, 1.4 KW (max. power 2.2 KW)
- Cooking zone middle: 240 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 190 mm, 210 mm, 2.2 KW (max power 3.7 KW)
- Cooking zone front right: 190 mm, 210 mm, 2.2 KW (max. power 3.7 KW)

Usage convenience

- Touch control: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- LED timer for each zone with switch off function and acoustic signal
- : an alarm sounds at the end of the time set (e.g. for pasta).

Time saving & efficiency

- Power Boost function for all zones
 : boil water faster thanks to 50% more energy than at the highest standard level.
- 2-steps: increase or decrease the power level simply by moving the pot forwards or backwards.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds

Safety

- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

Installation

- Dimensions of the product (HxWxD mm): 51 x 802 x 522
- Required niche size for installation (HxWxD mm) : 51 x 750 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- 4.6kW power output (20A); current management options for 16A, 13A or 10A connection: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, Cable included in packaging



